



BGT

-  Bocchetta in gomma con tappo rimovibile in silicone e ingresso sonda per C.O. (Ø 32 mm).
-  Rubber nozzle with silicon removable cap and intake for C.O. (Ø 32 mm).
-  Entonnoir en caoutchouc avec bouchon extractable en silicon et prise C.O. (Ø 32 mm).
-  Gummitrichter mit Verschlussdeckel und Anschluss für die Sonde C.O (DN 32 mm).
-  Boquerel de goma con tapa extraíble de silicona, y toma de CO (Ø 32 mm).

Model	for hose Ø mm	suction inlet Ø mm
BGT-75/140	75	140
BGT-100/140	100	140
BGT-125/140	125	140



BG-140

-  Bocchetta in gomma con ingresso sonda per C.O. (Ø 32 mm).
-  Rubber nozzle with intake for C.O. (Ø 32 mm).
-  Entonnoir en caoutchouc avec prise C.O. (Ø 32 mm).
-  Gummitrichter mit Anschluss für C.O. (DN 32).
-  Boquerel de goma con toma CO (Ø 32 mm).

Model	for hose Ø mm	suction inlet Ø mm
BG-75/140	75	140
BG-100/140	100	140
BG-125/140	125	140



BG-200

-  Bocchetta in gomma con ingresso sonda per C.O. (Ø 32 mm).
-  Rubber nozzle with intake for C.O. (Ø 32 mm).
-  Entonnoir en caoutchouc avec prise C.O. (Ø 32 mm).
-  Gummitrichter mit Anschluss für C.O. (DN 32).
-  Boquerel de goma con toma CO (Ø 32 mm).

Model	for hose Ø mm	suction inlet Ø mm
BG-75/200	75	200
BG-100/200	100	200
BG-125/200	125	200
BG-150/200	150	200
BG-180/200	180	200
BG-200/200	200	200